



# DeltaPS™ and DeltaTS™

## PIPESIZE and TELESCOPE Screens



### FEATURES:

- Slot sizing from 0.005" to 0.200"
- Materials: 304L or 316L stainless steel.
- Continuous slot rod base and pipe base constructions
- Shallow, intermediate and deep set designs available.
- Diameters: 1.25" to 20" diameters (pipe size and telescope size)
- Most standard fittings available

### BENEFITS:

- High strength minimizes chances for installation and development damage
- Continuous slot design maximizes flow rates
- Self cleaning design extends the life of the well
- Minimizes sand intrusion and pump wear

NOMINAL SIZE	SHALLOW DEPTH			OPEN AREA in <sup>2</sup> /ft (mm <sup>2</sup> /m)			
	OD	ID	Weight	SLOT OPENING SIZE: in (mm)			
				10 Slot (0.25mm)	20 Slot (0.50mm)	30 Slot (0.75mm)	40 Slot (1.0mm)
Unit	in (mm)	in (mm)	lb/ft (kg/m)	in <sup>2</sup> /ft (mm <sup>2</sup> /m)	in <sup>2</sup> /ft (mm <sup>2</sup> /m)	in <sup>2</sup> /ft (mm <sup>2</sup> /m)	in <sup>2</sup> /ft (mm <sup>2</sup> /m)
6P	6.63 (168)	6.00 (152)	6.6 (9.8)	23 (4500)	46 (9000)	69 (13500)	92 (18000)
8T	7.63 (194)	6.90 (175)	8.9 (13.2)	25 (5200)	53 (10400)	79 (15600)	105 (20800)
8P	8.63 (219)	7.90 (201)	10.0 (14.9)	30 (5800)	60 (11600)	89 (17400)	119 (23200)
10T	9.63 (244)	8.90 (226)	11.4 (17.0)	33 (6500)	67 (13000)	100 (19500)	133 (26000)
10P	10.75 (273)	10.00 (254)	12.5 (18.6)	37 (7300)	74 (14600)	112 (21900)	149 (29200)
12P	12.75 (324)	11.80 (300)	25.2 (37.5)	32 (6300)	64 (12600)	96 (18900)	128 (25200)
14P/16T	14.00 (356)	13.10 (333)	27.1 (40.3)	35 (6900)	70 (13800)	106 (20700)	141 (27600)
16P/18T	16.00 (406)	15.10 (384)	31.0 (46.1)	40 (7900)	80 (15800)	121 (23700)	161 (31600)
18P/20T	18.00 (457)	17.10 (434)	34.6 (51.5)	45 (8900)	90 (17800)	136 (26700)	181 (35600)
20P	20.00 (508)	19.10 (485)	38.6 (57.4)	50 (9800)	101 (19600)	151 (29400)	201 (39200)

NOMINAL SIZE	INTERMEDIATE DEPTH			OPEN AREA in <sup>2</sup> /ft (mm <sup>2</sup> /m)			
	OD	ID	Weight	SLOT OPENING SIZE: in (mm)			
				10 Slot (0.25mm)	20 Slot (0.50mm)	30 Slot (0.75mm)	40 Slot (1.0mm)
Unit	in (mm)	in (mm)	lb/ft (kg/m)	in <sup>2</sup> /ft (mm <sup>2</sup> /m)	in <sup>2</sup> /ft (mm <sup>2</sup> /m)	in <sup>2</sup> /ft (mm <sup>2</sup> /m)	in <sup>2</sup> /ft (mm <sup>2</sup> /m)
6P	6.63 (168)	6.00 (152)	6.6 (9.8)	23 (4500)	46 (9000)	69 (13500)	92 (18000)
8T	7.63 (194)	6.90 (175)	8.9 (13.2)	25 (5200)	53 (10400)	79 (15600)	105 (20800)
8P	8.63 (219)	7.70 (196)	17.1 (25.4)	22 (4200)	43 (8400)	65 (12600)	87 (16800)
10T	9.63 (244)	8.70 (221)	19.3 (28.7)	24 (4700)	48 (9400)	73 (14100)	97 (18800)
10P	10.75 (273)	9.80 (249)	21.4 (31.8)	27 (5300)	54 (10600)	81 (15900)	108 (21200)
12P	12.75 (324)	11.80 (300)	25.2 (37.5)	32 (6300)	64 (12600)	96 (18900)	128 (25200)
14P/16T	14.00 (356)	13.10 (333)	27.2 (40.5)	35 (6900)	70 (13800)	106 (20700)	141 (27600)
16P/18T	16.00 (406)	15.00 (381)	34.4 (51.2)	29 (5700)	59 (11400)	88 (17100)	118 (22800)
18P/20T	18.00 (457)	17.00 (432)	38.4 (57.1)	33 (6500)	66 (13000)	99 (19500)	132 (26000)
20P	20.00 (508)	19.00 (483)	42.9 (63.8)	37 (7200)	74 (14400)	110 (21600)	147 (28800)

[www.deltascreens.com](http://www.deltascreens.com)

P.O. Box 842397 Houston, Texas 77284

main: 713-856-0300 fax: 713-856-0303