



DeltaDirect™ WRAP ON PIPE SCREEN



FEATURES:

- Internal quality control of wrap wire specifications.
- Screens are available in standard service 316LSS or CRA alloys as required.
- Screen to base pipe attachment method provides maximum strength to withstand high loads in shear, compaction and torque.
- Wire dimensions and configurations are available for specific requirements varying from stand alone, OHGP, HRWP or FP deployments.
- Available in Range 3 lengths.

BENEFITS:

- Suitable for high angle or short radius horizontals such as multi-lateral deployments.
- A more cost effective alternative to premium diffusion bonded screens when applicable.
- Suitable for stand alone, cased hole, open hole and horizontal completions.
- Inherently damage resistant due to the manufacturing process of directly wrapping to base pipe.

SIZE	BASE PIPE						Inlet Area					
	A	B	C		D	F	G		H	I		
	OD	Coupling OD	Weight	ID	Max. Perforation - Flow Area		Product		Base Pipe Flow	.006" Slot	.008" Slot	.012" Slot
Unit	in	in	lb/ft	in	Size (in)	in ² /ft	lb/ft	Max. OD (in)	in ²	(sq. in/ft)		
2-3/8"	2.375	2.875	4.6	1.995	0.375	5.299	8.50	2.91	3.126	6.857	8.955	12.906
2-7/8"	2.875	3.500	6.4	2.441	0.375	5.299	11.00	3.41	4.678	8.035	10.494	15.124
3-1/2"	3.500	4.250	9.2	2.867	0.375	6.624	15.00	4.05	6.456	9.543	12.464	17.963
4"	4.000	4.750	11.6	3.428	0.375	7.949	18.00	4.55	9.229	10.721	14.003	20.180
4-1/2"	4.500	5.000	13.5	3.920	0.375	9.274	21.50	5.06	12.069	11.922	15.572	22.442
5"	5.000	5.563	15.0	4.408	0.375	9.274	22.50	5.56	15.261	13.100	17.111	24.660
5-1/2"	5.500	6.050	17.0	4.892	0.375	10.598	25.25	6.07	18.796	14.302	18.680	26.922
6-5/8"	6.625	7.390	24.0	5.921	0.375	11.923	34.00	7.20	27.535	16.965	22.158	31.933
7"	7.000	7.657	23.0	6.366	0.375	13.248	34.00	7.58	31.829	17.860	23.327	33.619



- C** - Base Pipe Inner Dimension
- D** - Base Pipe Perforation Diameter
- F** - Max. Perforation Flow Area
- H** - Base Pipe Flow Area
- I** - Inlet Area

www.deltascreens.com

P.O. Box 842397 Houston, Texas 77284
 main: 713-856-0300 fax: 713-856-0303