



DeltaWeld™ THRU-TUBING SCREEN



FEATURES:

- Internal control of wire specifications and quality.
- Complete range of sizes including TT applications.
- Jackets available in standard service 316LSS or CRA alloy as required.
- Wire dimensions and configurations are available for various applications from stand alone to GP deployments.
- Wire profiles available for heavy duty design for maximum erosion resistance.

BENEFITS:

- Minimum product lead times.
- Most cost effective screen alternative.
- Suitably designed for stand alone as well as cased hole, open hole and gravel pack completions.
- Strong base pipe attachment to withstand high mechanical loads.

Specifications	
Blank Length	Pin - 4" min
Blank Length	Box - 4" min
Connection	NU 10RD T&C
Basepipe Metallurgy	L-80
Overall Assembly Length	6, 8, 10 ft
Metallurgy Filter Media	316L/A20

A	B	C	D	E	Tensile Strength	Collapse Strength	Burst Strength
Basepipe OD	Basepipe ID	Coupling OD	Screen OD	Screen Gauge	lbs	psi	psi
in	in	in	in	in			
1.315	1.049	1.660	1.680	.008	2600	4390	1280
1.660	1.380	2.054	2.030	.008	3640	2520	1064
1.900	1.610	2.200	2.240	.008	4160	1805	952
2.063	1.751	2.500	2.430	.008	4860	1450	885

